

TrueMobile APEX



49" (125 cm)

47.2" (120 cm)



22.8" (58 cm)



POWER

- 100-240 VAC (+/- 10%), 50/60 Hz

X-RAY CHARACTERISTICS

- 32 kW at 100 mS or 40 kW at 10 mS
- 40-125 or 40-133 kVp
- 0.1-320 mAs
- 0.6/1.3mm focus size
- 13,5 deg Anode Angle
- 212 KHU

MOVEMENT RANGE

- 53-195 cm (20,8"-76,8") SID to floor (option 200 cm)
- 134 cm (52,8") Tube arm reach total
- +/- 270 deg Rotation of telescopic arm
- +/- 180 deg Tube Rotation
- -10 to +90 deg Tube Tilt

EXAMVUE™ APEX WIRELESS DETECTOR

- Sizes:
 - EVA10W: 10" x 12"
 - EVA14W: 14" x 17"
 - EVA17W: 17" x 17"
- IP67: water & dust resistant
- Automatic detector charging when stored inside the Mobile Unit
- Integrated detector and grid storage in Mobile Unit

** Contact JPI sales representative for detailed technical specifications of ExamVue Apex detectors.*

SIZE & WEIGHT

- Weight 714 lbs (324kg)
- Length (body) 44,5" (113 cm)
- Length (with handle) 49" (125 cm)
- Width 22,8" (58 cm)
- Height (park/transport) 47,2" (120m)

USER INTERFACES

- Monitor:
 - 17" TFT - LCD LED
 - 1280 x 1024
 - 16.7 M colors
 - Viewing angle (Typ) 178 deg
- Touchscreen: Capacitive
- Adjustable height of drive handle: 4,7" (120 mm)
- Indication lights: sides and column top
- Precision drive joystick: body and tube head
- Collision protection: front, tube and monitor

OPTIONS

- Wireless remote control for exposure & collimator light
- Dose Area Meter (integrated inside collimator)
- Tube head display: iPad application & mount
- Detector lock
- Automatic collimator filters
- 78,7" (200cm) SID to floor
- Software grid: scatter correction
- Pediatric version: color scheme



X-tech Cell Battery Performance

- ▶ Operating time: **Up to 9 hours**
- ▶ Charging from empty to full: **1.5 hours**



Contact us:

100-B Executive Dr, Edgewood, NY 11717
 sales@jpihealthcare.com
 (516) 513-1330 Ext. 3

